



- Specification :
- 1. Rated voltage: DC. 12V 50mA
 - 2. Contact Resistance: 100mΩ (Max)
 - 3. Insulation resistance: 100MΩ (Min) DC250V
 - 4. Dielectric strength: AC250V (50-60Hz) for 1 minute
 - 5. Operation force: 95±20gf
 - 6. Full Travel: 0.25±0.15mm
 - 7. Life Test :1, 000, 000 Cycles (min)

ITEM	PART NAME	TERNO.	QTY.	MATERIAL	FINISHING	REMARK
⑨	Terminal	4	1	BRONZE(O.15t)	Plating Silver	
⑧	Terminal	3	1	BRONZE(O.15t)	Plating Silver	
⑦	Terminal	2	1	BRONZE(O.15t)	Plating Silver	
⑥	Terminal	1	1	BRONZE(O.15t)	Plating Silver	
⑤	Shell		1	Stainless Steel		
④	Contact		1	Stainless Steel	Plating Silver	
③	Base		1	Nylon	Black	
②	Rubber Pad		1	Rubber	Purple	
①	Keystoke		1	Nylon	Black	

APPROVALS		DATE	TITLE:	
DRAWN	Chen Geng	2019. 05. 13	TA6235轻触开关	
CHECKED			Kailih	
APPROVALS			DONGGIAN CITY KAILIH ELECTRONICS CO.,LTD	
			东莞市凯华电子有限公司	
			PART NO. CT A623501A01	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A1		NEW			

TOLERANCES	ANG	SCALE:	DRAWING NO.	SHEET
30±0.30	±2°	1:1		1 OF 1
10±0.20				
5±0.15				
1±0.10				